



P.J. POOL PLASTERING

PLASTERING POOLS VICTORIA WIDE

1300 30 47 11

www.pjpoools.com.au

ABN 90 450 083 079

factory 9 22-24 rhur street dandenong south victoria 3175 australia F 03 9792 2955

RBP Registered Building
Practitioner
Number 16612



AQUANEON CUSTOMER CARE GUIDE

Congratulations! You now own the best concrete pool interior surface available.

To maximize your enjoyment of the pool, we have listed below some helpful tips on pool maintenance, along with the recommended water chemical balance parameters for your new luxury finish. If you will be taking water samples to a pool shop for testing, **take this form with you along with the dimensions of your pool.**

FILL THE POOL IMMEDIATELY & BALANCE THE WATER CHEMISTRY

	<u>Recommended Level</u>
pH	7.2 - 7.4
Total Alkalinity mg/L	120 - 130
Free Chlorine	1.0 - 2.0
Total Hardness mg/L	150 - 200

- ◆ These levels should be achieved as soon as possible for swimmer comfort and hygiene.
- ◆ These levels are a guide only.
- ◆ Any sediment should be vacuumed to waste.
- ◆ All automatic cleaners can be fitted immediately. Suction type cleaners are the best – e.g. Barracuda, Kreepy Krauly.
- ◆ Over the course of the first week, stabilize pH (using acid & buffer), Total Alkalinity. Add “sunscreen” and sanitizer (usually chlorine). All chemistry levels should be checked and adjusted WEEKLY.
- ◆ If a salt pool, delay addition of salt until all other levels have been achieved. (minimum of 4 weeks)
- ◆ If no auto-cleaner is used, pool should be brushed and vacuumed WEEKLY by hand.

- ◆ This surface is very tough and stain resistant, if however organic stains from rotting leaves or the like are experienced – sprinkle dry chlorine over the stain and it will disappear in a few minutes. Pour down a tube onto stain if in deep water.
- ◆ For metal stains e.g. rusting nail – purchase proprietary chemicals designed to suit the problem and follow manufacturer's directions.
- ◆ Each pool chemical should be diluted in a bucket with water and “broadcast” over pool's surface.
- ◆ Never mix different chemicals together.
- ◆ Always read and follow manufacturer's directions when using pool chemicals.
- ◆ Run your filter for 8 hours a day, backwash regularly – follow manufacturer's directions.
- ◆ Never drain the pool without contacting PJ Pool Plastering or the Aquaneon installer FIRST – failing to do this will void all warranties on product and installation.